



# DA-200

## 1x4 Distribution Amplifier ASI, 3G & HD/SD-SDI



1 auto-sensing input, 75 ohm BNC connector

Input signal lock detection LED

4 re-clocked outputs, 75 ohm BNC connector

SD/HD Status LED

Data rates from 270 Mbps to 3 Gbps

Use with encoders, analyzers and other compliant equipment

Ultra compact, reliable, cost effective solution

Comes complete with power supply

LED Power Indicator

### DESCRIPTION

The **DA-200** is a compact multi-rate re-clocking distribution amplifier for use as a point-to-multipoint distribution hub of signals around your facility or an inline repeater to extend the signal over greater distances.

The **DA-200** provides automatic input detection, re-clocking and cable equalization at 0.270, 1.485 and 2.97 Gbps.

The **DA-200** passes embedded audio, ancillary ID and metadata information.

The **DA-200** has a small form factor replacing rack mounted equipment frames saving valuable rack space. The **DA-200** is a simple and cost effective solution.

### SPECIFICATIONS

#### Formats

DVB-ASI:	270 Mbps
SMPTE 259M:	270 Mbps
SMPTE 292M:	1.485 Gbps
SMPTE 424M:	2.97 Gbps



Made in the USA

**VISION + INNOVATION**

DTV Innovations | 1252 W. Northwest Hwy. | Palatine, IL 60067 | 847.919.3550 | [www.dtvinnovations.com](http://www.dtvinnovations.com)